

Dynstorm A/T - Dimension Data (TR/HR/VR/WR 65/70/75/80/85)

▼ Currently under development.  Print

SER	Size	P.R.	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	Max PSI	Max Load	
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS
65	P215/65R16	98H															
	255/65R16	109H															
	235/65R17	105H															
	245/65R17	107H															
	265/65R17	113S															
	275/65R17	115T															
70	P205/70R15	96S															
	P235/70R15	102S															
	P215/70R16	100S															
	P225/70R16	101S															
	P235/70R16	105S															
	P245/70R16	107S															
	P255/70R16	111S															
	P265/70R16	112S															
	LT275/70R16	112/109Q															
75	LT215/75R15	100/97Q															
	P225/75R15	102S															
	LT235/75R15	104/101Q															
	P235/75R15	105S															
	LT225/75R16	110/107Q															
	LT245/75R16	120/116Q															
	LT265/75R16	119/116Q															
	LT285/75R16	112/119M															
80	LT30*9.5R15	104S															
	LT31*10.5R15	109Q															
	P195/80R15	94S															
	LT205/80R16C	110/108Q															
	LT215/80R16	104/101Q															
85	LT215/85R16	110/107S															
	LT235/85R16	120/116Q															

*These data can be changed by manufacturer without prior notice.